

DEC 5

Decoupling Network for Symmetrical Data and Control Lines

■ The **DEC 5** is used for decoupling auxiliary equipment from an EUT tested with either 1,2/50µs - 8/20µs combination wave impulses or 10/700µs impulses up to 6.6kV peak. It is used to decouple unshielded symmetrical data and signal lines according standards IEC 61000-4-5 Edition 1 and 2 and ITU K.44. Up to 4 wires can be tested simultaneously.

To obtain maximum flexibility only decoupling and protection elements are included in the DEC 5. Coupling circuits, which depends on the EUT to be tested, can be placed separately in the test setup.

Manual coupling selection of the protection elements for best protection of the auxiliary equipment.

Default protection elements are gas arrestors and breakdown avalanche diodes. With such elements the capacitive load to the EUT lines is small. The decoupling elements can be selected easily. It is also possible to test without any protection elements.

The DEC 5 can be used together with the coupling networks PCD 120, PCD 121, PCD 122, PCD 800, PCD 900 and IP6.2. These provide all the coupling elements as required to perform IEC, ANSI and EN testing.

With a 100 year history of innovation, service centers on three continents and a full staff development and support engineers, HAEFELY HIPOTRONICS is the clear choice for all your transient immunity test needs.



FEATURES

- Inductors 20mH compensated
- Combination wave 1,2/50us - 8/20us impulses
10/700us telecom impulses
- 100kHz ring wave impulses
- Breakdown avalanche diodes and gas arrestors as protection elements
- Up to 4 wires can be tested
- Signal Bandwidth up to some 100kHz

BENEFITS

International application – Specifically designed to meet and exceed the requirements of:

- IEC / EN 61000-4-5 Edition 1: Figure 12
- IEC / EN 61000-4-5 Edition 2: Figure 14
- IEC / EN 61000-4-12 Edition 2: Figure 12
- ITU K.44: 2003 Figures A.5-1, A.6.1-1 to A.6.1-5

Safe and Easy – All the sockets are safety banana plugs to ensure maximum safety to the user. The selected protection element can be seen at a glimpse.

Sturdy and Reliable – Careful component selection ensures that the DEC 5 will continue to operate under the most strenuous testing regimen.

Report Generation – The unit controller can automatically generate test reports without a computer. Add WinFEAT&R control and reporting software on a host PC to collect and collate data in any format you like.

