



## EVD Series High Precision Bidirectional DC Power Supply

- Constant DC voltage output
- Step mode/Gradient mode
- Editable overvoltage/overcurrent protection point
- Editable voltage drop/rise slew rate
- Voltage compensation
- External emergency stop

### Summary

EVD Series High Precision Bidirectional DC Power Supply is a high precision DC power supply adopting two-stage conversion architecture, featuring high dynamic response, and bidirectional energy flow. Ideal match for E-motor (controller) testing, powertrain system testing etc. For E-motor testing, EVD can be used to simulate the overload capacity, efficiency, locked-rotor current, maximum speed, overspeed, and energy recovery performance of the electric motor and controller.

### Advantages

- Wide voltage and current output
- High precision and resolution
- High dynamic response in 3-6ms
- Multi-filtering solutions
- Superposition of ripple (Optional)
- Fast CAN communication: 1ms
- Standard communication interfaces: RS485, CAN, LAN, Ether CAT (optional)



### HEFEI KEWELL POWER SYSTEM CO., Ltd.

Hefei Headquarters: 0551-65837951    Beijing Branch: 010-87514122    Shanghai Branch: 021-69897355    Shenzhen Branch: 0755-23205180  
 Xi'an Branch: 029-86691696    Nanjing Branch: 025-86557702    Chongqing Office: 023-65869858    Taiwan Agency: +886-2506-0980  
 Germany Agency: +49 (0) 30 / 20 67 48 35    Korea Agency: +82-31-737-4754

### Specifications

Specifications Model						
Models	Rated Power [kW]	Rated Current [A]	Rated Voltage [V]	Peak Power (60s)[kW]	Peak Current (60s)[A]	Voltage Range* [V]
EVD-80-1000	80	300	266	120	450	24-1000
EVD-100-1000	100	350	285	150	525	24-1000
EVD-150-1000	150	500	300	200	666	24-1000
EVD-200-1000	200	600	333	250	750	24-1000
EVD-250-1000	250	600	416	350	840	24-1000
EVD-300-1000	300	750	400	400	1000	24-1000
EVD-400-1000	400	1000	400	500	1250	24-1000
EVD-500-1000	500	1200	416	600	1440	24-1000

\*Rated voltage of each model above is also available in 800V and 1200V. High voltage standard product is also available in 1500V and 2000V, with dual channel.

Input Requirements	
Phase	3φ3W + PE
Voltage	380V±15%
Frequency	50Hz±5Hz

Feedback Characteristics	
Energy Recovery	Energy recovery is available in full power range
THD	≤3%
Power Factor	≥0.99

Communication Interfaces	
Local Interface	LCD
Remote Comms	RS485/LAN /CAN
Others	External Emergency Stop/ Fault Signal/Voltage Compensation

Output Characteristics	
Voltage Precision	± (0.1%-FS+5dgt)
Current Precision	± (0.1%-FS+5dgt)
Response Time	≤3ms(10%-90%)
Switching Time	≤6ms( + 90% - -90%)
Voltage Ripple (rms)	≤0.2%-FS
Load Regulation	0.1%-FS
Protection	Overvoltage/Overcurrent/Overtemp./Phase Loss/Emergency Stop

Safety & Ambient Conditions	
Insulation Resistance	≥20MΩ(500Vdc)
Withstand Voltage	2000V DC (60s, no arch/break down)
Ground Resistance	≤0.1Ω
Protection Level	IP21 (Indoor)
Cooling	Fan Cooling
Ambient Temperature	-10 ~ 40°C
Relative Humidity	0-90%RH (Non-condensing at 25°C)
Altitude	≤2000m

### Software Interface

Available with three output modes: General Mode, Step Mode, Gradient Mode



General Mode



Gradient Mode